Symbol X



HIGH-PERFORMANCE MULTI-FUNCTIONAL SPEAKERS (IPX 5 CERTIFIED)

Magnat

Symbol X







HIGH-PERFORMANCE MULTI-FUNCTIONAL SPEAKERS (IPX 5 CERTIFIED)

- Speakers for home audio and professional PA systems
- Home-recording monitor speakers
- Indoor/Outdoor bookshelf speakers
- Splash-proof by IPX5 standard, corrosion-resistant materials
- Integrated wall mounting device, horizontally and vertically adjustable
- Perfect sound and very high power handling

Magnat

Symbol X









SPLASH-PROOFED HOUSING

Speaking of the housings, they are not only timelessly elegant, but also extremely functional. IPX5 certification means that the Symbol X can be subjected to splash water without any problems.

CLEVER HOUSING CONSTRUCTION

The integrated wall bracket not only allows the speaker to be installed securely, but it also allows it to be aligned horizontally and vertically to the listening position. Thanks to the integrated mounting options, it works perfectly both indoors and outdoors on walls, columns or pillars – out of the way, but always unmistakable.

RESILIENT SPEAKER TECHNOLOGY


Each Symbol X incorporates a fully-fledged twoway system. The powerful polyethylene tweeters with their neodymium drives are complemented by a 140 mm or 165 mm bass-midrange driver with polypropylene diaphragm and a suspension that enables long strokes and a high dynamic range.

Magnat

Symbol X







HIGH-PERFORMANCE MULTI-FUNCTIONAL SPEAKERS (IPX 5 CERTIFIED)

DRIVERS


- PET dome tweeter with powerful neodymium magnet system
- High-performance woofer-midrange with polypropylene membrane and long-throw rubber surround

CABINET

- IPX 5 certified, splash-proof
- Solid low-resonance plastic housing with corrosion-resistant front grille
- Bass reflex design
- Integrated wall mounting device allows horizontal and vertical adjustment

CROSSOVER

- Elaborated phase and amplitude optimized crossover with high-quality components
- High-quality connecting terminal with solid, gold-plated and capsulated screw connectors
- Dynamic overload protection









Symbol X

SYMBOL X 130

2-way speaker with bass reflex technology

DRIVERS

1 x 5.25" woofer- midrange, 3/4" dome-tweeter

POWER HANDLING (RMS/MAX)

90 / 200 watts

IMPEDANCE

4 - 8 ohms

FREQUENCY RESPONSE

34 - 36.500 Hz

CROSSOVER FREQUENCIES

3.800 Hz

RECOMMENDED AMPLIFIER OUTPUT

20 - 200 watts

SENSITIVITY

90 dB

PROTECTION CLASS

IPX 5

CABINET SURFACE

Black, White

DIMENSIONS (WxHxD) WITHOUT WALL MOUNTING

151 x 249 x 197 mm

WEIGHT

2.4 kg

ART.NO./EAN

Black: 168 410 / 40 18843 68410 9 White: 168 415 / 40 18843 68415 4



SYMBOL X 160

2-way speaker with bass reflex technology

DRIVERS

1 x 6.5" woofer- midrange, 1" dome-tweeter

POWER HANDLING (RMS/MAX)

110 / 220 watts

IMPEDANCE

4 – 8 ohms

FREQUENCY RESPONSE

30 – 36.500 Hz

CROSSOVER FREQUENCIES 3.400 Hz

RECOMMENDED AMPLIFIER OUTPUT

20 - 220 watts

SENSITIVITY

92 dB

PROTECTION CLASS

IPX 5

CABINET SURFACE

Black, White

DIMENSIONS (WXHXD) WITHOUT WALL MOUNTING

186 x 310 x 242 mm

WEIGHT

3.3 kg

ART.NO. /EAN

Black: 168 400 / 40 18843 68400 0 White: 168 405 / 40 18843 68405 5

